

# CAPTILE WALLGROUT

## WHITE OR PIGMENTED JOINT FILLER

### DESCRIPTION

**CAPTILE WALL GROUT** is a blend of selected cements, fillers, proprietary chemicals and high quality pigments. **CAPTILE WALL GROUT** is used to fill tile joints of width less than 4mm.

### COLOUR

White, grey and 20 other standard colors.  
Shade card available on request.

### USES

For grouting tile joints of ceramic, glass, mosaic, and vitreous lining. Suitable for internal and external applications. **CAPTILE WALL GROUT** should not be used in areas subject to strong acids. This can be used where an exceptionally high standard of hygiene is essential as in food processing areas, pharmaceutical industries, operation theater, pathological laboratory etc.

### ADVANTAGES

- Excellent workability.
- Low shrinkage.
- Good adhesion to the joint sides.
- Excellent resistance to mold growth and bacteria.
- Excellent coverage.
- Very pliable and easy to apply.

### PROPERTIES

Pot life : Approx. 40 minutes at 25°C.

### APPLICATION INSTRUCTIONS

#### Surface preparation:

Grouting must be performed over properly adhered tiles. Ensure that the joint to be grouted is sufficiently clean. Excess mortar in joints must be removed.

#### Mixing:

Mix 3 parts of **CAPTILE WALL GROUT** with one part water by weight until a thick creamy paste is produced. For a stiffer grout use slightly less water. Allow to stand for 5 minutes before use. Add **CAPTILE WALL GROUT** to water. Be consistent in the amounts of mixing liquid used.

Do not add additional water to re temper the material.

Alternatively to enhance grout properties such as adhesion, flexibility, water resistance and frost Resistance use **CAPTILE LATEX** diluted with equal volume of water in place of gauging water at the dosage rate of 2.5 to 2.75 ltrs/10 kg of **CAPTILE WALL GROUT**. **CAP TILE LATEX** will enhance the color intensity of pigmented grout.

#### Application:

For unglazed tiles, dampen the surface prior to grouting, but do not leave water in the joint spaces. Diagonally press material into space between joints with an appropriate grouting float, sponge or soft cloth to ensure complete filling of the joint.

#### Finishing:

Once the grout has acquired an initial set, smooth the joints and remove the grout haze from tile with a slightly dampen soft cloth, and finally polish off with a dry cloth. Do not allow to dry on textured surfaces.

#### Cleaning:

**CAPTILE WALL GROUT** should be removed from tools, equipment and mixers with clean water immediately after use.

#### Note:

Always apply a test sample in a hidden area to evaluate performance, prior to entire application.

### COVERAGE

Coverage depends on the type, size and spacing of tiles.

### PACKAGING

**CAPTILE WALL GROUT** is supplied in 10 kg bags.

### STORAGE

**CAPTILE WALL GROUT** should be stored over pallet in a cool dry place. Shelf life will be 12 months in unopened bags.

# CAPTILE WALLGROUT

## WHITE OR PIGMENTED JOINT FILLER

### SAFETY PRECAUTIONS

**CAPTILE WALL GROUT** does not contain toxic materials. Care should be taken to avoid inhalation of dust and to prevent material entering in

.

.

#### TECHNICAL SERVICE:

Our Technical Service Department is available at any time to advise you in the correct use of this product or any other Ahlia products.

**Note :** The information presented herein is based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture, no specific guarantee can be extended because results depend not only on quality but also on other factors beyond our control.

**As all Ahlia Technical Data Sheets are updated on a regular basis, it is the user responsibility to collect most recent issue.**